
LÜLSBERG

Roband Frypod

Features

- Removable electronics/heating elements and exchangeable GN containers - less risk of injury and more comfortable cleaning
- Heating elements swing back with two locking positions (one for dripping off the oil, the other one for removal of the GN container)
- "Smart Lock" safety mechanism: Prevents removal of electronics when machine is on and switching on the machine when electronics are removed
- Precise thermostat control up to max. 190°C





- Safety over-temperature cut-out
- High splashguard (oil is returend into the container this saves oil and keeps the kitchen clean)
- Modern brushed stainless steel finish
- Max & min oil level markers



Draining position



Position for removing the GN container



Electronics have been removed for cleaning the fryer

Model	Tank (Litres)	Current (Amps)	Power (Watts)	Dimensions WxDxH (mm)	Weight (kg)
FR15-F	5	16	2300 (2900)	290 x 480 x 335	11
FR25-F	2 x 5	2 x 16	2 x 2300 (2900)	570 x 480 x 335	17

220-240V 50-60Hz **(**€

ROBAND 🔤

Roband Australia Pty Ltd, 1 Inman Road, Cromer, NSW 2099 Australia Tel: +61 2 9971 1788 Fax: +61 2 9971 1336 Email: roband@roband.com.au www.roband.com.au

distributed by LÜLSBERG

LÖLSBERG, Inh. Bernd Lölsberg Otto-Hahn-Straße 9a 97230 Estenfeld Deutschland Tel: +49 (0) 9305 98978-0 Fax: +49 (0) 9305 98978-88 Email: info@loelsberg.de www.loelsberg.de

our contact:		
		0519
		0317

